Christopher North Builders

PO Box 770275

Naples Florida 34107

239-825-9155

chrisnorthnaples@gmail.com



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: Jan 27, 2022								
Owner Information								
Owner Name: Lipic, Joe Contact Person:								
Address: 100 North Collier Boulevard #	900	Home Phone:						
City: Marco Island	Zip: 34145	Work Phone:						
County: Collier		Cell Phone:						
Insurance Company:		Policy #:						
Year of Home: 1989	# of Stories: 1	Email:						

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

- 1. <u>Building Code</u>: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
 - A. Built in compliance with the FBC: Year Built _____. For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY) ___/ /___/
 - B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built _____. For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY) ___/__/
 - C. Unknown or does not meet the requirements of Answer "A" or "B"
- <u>Roof Covering:</u> Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
1. Asphalt/Fiberglass Shingle	/			
2. Concrete/Clay Tile	/			
3. Metal	//			
4. Built Up	/			
5. Membrane	2-23-21		2021	
6. Other	/			

- A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
 - B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
 - C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
 - D. No roof coverings meet the requirements of Answer "A" or "B".

3. <u>Roof Deck Attachment</u>: What is the <u>weakest</u> form of roof deck attachment?

A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.

B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.

C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Inspectors Initials _____ Property Address 100 North Collier Boulevard #900 _____ Marco Island 34145

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.

				orm is valid for up to five (5) years provided no material changes have been made to the structure or on the form.	
Inspe	ecto	rs]	Initials	Property Address 100 North Collier Boulevard #900 Marco Island 34	145
		6 3. 1	lwelling No SWR.	g or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.	
6. <u>S</u>		A. S	SWR (als	er Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to	the
] (C. (Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.	
	-		Flat Roof	Total length of non-hip features: feet; Total roof system perimeter: feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of	
	ie ho	ost		over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).	01
] H	I. 1	No attic a		lof
			Other:	n or unidentified	
\boxtimes	E	E. S	Structural		
				a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall o both sides, and is secured to the top plate with a minimum of three nails on each side.	n
				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with	th
Г	1 с) .]	Double V	minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.	11 a
] (C. S	Single W		h a
				Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the position requirements of C or D, but is secured with a minimum of 3 nails.	nail
	JE	3. (Clips	Metal connectors that do not wrap over the top of the truss/rafter, or	
	1 -			Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ¹ / ₂ " gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.	n
				Secured to truss/rafter with a minimum of three (3) nails, and	
Μ	liniı	mal	لـــا conditic	ons to qualify for categories B, C, or D. All visible metal connectors are:	
				Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D	1 to
	feet	t of		tachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks wit le or outside corner of the roof in determination of WEAKEST type)	nın
	-		No attic a		
	_			or unidentified.	
	-		Reinforce Other:	ed Concrete Roof Deck.	
	- 1		P		

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Opening Protection: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

•	ening Protection Level Chart		Non-Glazed Openings				
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		\times	\mathbf{X}	\mathbf{X}		X
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)	X				\times	
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
х	No Windborne Debris Protection						

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, <u>and</u> 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above

A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above

B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):

- ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 4.5 lb.)
- SSTD 12 (Large Missile 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)

B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist

B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

\square	C.	Exterior	0	pening	Protection-	Wood	Structural	Panels	meeting	FBC	2007	All	Glazed	openings	are	covered	with
					the requirem												

٦	C.1 All Non-Glazed	d openings classified	as A, B, or C in the	e table above, or no	Non-Glazed	openings exist
---	--------------------	-----------------------	----------------------	----------------------	------------	----------------

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors InitialsProperty Address	100 North Collier Boulevard #900	Marco Island	34145

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

N. Exterior Opening Protection (unverified protective coverings not meeting the required with no documentation of compliance (Level	ments of Answer "A", "B", or G							
N.1 All Non-Glazed openings classified as Lev	,	or no Non-Glazed openings exist						
N.2 One or More Non-Glazed openings classifit table above			l X in the					
N.3 One or More Non-Glazed openings is class	sified as Level X in the table above							
X. None or Some Glazed Openings One or	more Glazed openings classifie	ed and Level X in the table above.						
	NS MUST BE CERTIFIED BY. ututes, provides a listing of indi	4 QUALIFIED INSPECTOR. viduals who may sign this form.						
Qualified Inspector Name: Chris North	License Type: CGC	License or Certificate #: 1506189						
Inspection Company: Christopher North Builders		Phone: 239-825-9155						
Qualified Inspector – I hold an active lic	ense as a: (check one)]					
Home inspector licensed under Section 468.8314, Fl training approved by the Construction Industry Lice	lorida Statutes who has completed nsing Board and completion of a p	•	igation					
Building code inspector certified under Section 468. General, building or residential contractor licensed u								
		utes.						
	ofessional engineer licensed under Section 471.015, Florida Statutes. ofessional architect licensed under Section 481.213, Florida Statutes.							
Any other individual or entity recognized by the inst		alifications to properly complete a uniform mi	tigation					
verification form pursuant to Section 627.711(2), Fl			ugution					
under Section 471.015, Florida Statues, must ins Licensees under s.471.015 or s.489.111 may auth experience to conduct a mitigation verification in I, am a qualified (print name) contractors and professional engineers only) I had and I agree to be responsible for his/her work. Qualified Inspector Signature: An individual or entity who knowingly or throug subject to investigation by the Florida Division of appropriate licensing agency or to criminal pros certifies this form shall be directly liable for the	orize a direct employee who p nspection. inspector and I personally per d my employee ((prin Date <u>gh gross negligence provides a</u> of Insurance Fraud and may b ecution. (Section 627.711(4)-('	cossesses the requisite skill, knowledge, cformed the inspection or (<i>licensed</i>) perform the inspection t name of inspector) : Apr 28, 2021 false or fraudulent mitigation verificat e subject to administrative action by th 7), Florida Statutes) The Qualified Insp	and tion form is te tector who					
Homeowner to complete: I certify that the name residence identified on this form and that proof of it Signature:		e or my Authorized Representative.	of the					
An individual or entity who knowingly provides obtain or receive a discount on an insurance pre of the first degree. (Section 627.711(7), Florida S	mium to which the individual							
The definitions on this form are for inspection parts as offering protection from hurricanes.	urposes only and cannot be us	ed to certify any product or construction	on feature					
Inspectors Initials Property Address 100	North Collier Boulevard #90	0 Marco Island	34145					
*This verification form is valid for up to five (5) inaccuracies found on the form.			or					

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155













































